## μS/mS/TDS Meter



SPECIFICATIONS		HI 8033
Dango	EC	0.0 to 199.9 µS/cm; 0 to 1999 µS/cm; 0.00 to 19.99 mS/cm
Range	TDS	0 to 19990 mg/L (ppm)
Resolution	EC	0.1 µS/cm; 1 µS/cm; 0.01 mS/cm
Resolution	TDS	10 mg/L (ppm)
Accuracy (@20°C/68°F)		$\pm 1\%$ F.S. (excluding probe error)
Calibration		manual, one point
Temperature Compensation		manual, 0 to 50°C (32 to 122°F) with $\beta$ =2%/°C
Probe		HI 76301W conductivity probe with 1 m (3.3') cable (included)
Battery Type / Life		9V / approximately 100 hours of continuous use
Environment		0 to 50°C (32 to 122°F); RH max 95%
Dimensions		185 x 82 x 47 mm (7.3 x 3.2 x 1.9")
Weight		270 g (9.5 oz.)

- Potentiometric technology
- Three conductivity ranges and one TDS
- Accurate and reliable
- Easy to clean probe

HI 8033 is a handheld conductivity meter with the ability to take measurements in three different ranges.

The included HI 76301W probe utilizes the four-ring potentiometric method which measures conductivity with the utmost accuracy and reliability.

The four stainless steel rings are embedded in the resin shaft of the probe to create a smooth surface for fast and easy cleaning.

To improve accuracy in measurements, temperature compensation can be achieved with a knob on the front panel of the meter.

The dial on the front of the HI 8033 easily indicates which range you are working in.





HI 710010 Shockproof Boot

HI 710001 Soft Carrying Case

## ORDERING INFORMATION

**HI 8033** is supplied with HI 76301W conductivity probe, calibration screwdriver, battery and instructions.

PROBES			
HI 76301W	Four ring conductivity probe with 1 m (3.3') cable		
SOLUTIONS			
HI 7030L	12880 µS/cm calibration solution, 500 mL		
HI 7031L	1413 µS/cm calibration solution, 500 mL		
HI 7032L	1382 mg/L (ppm) calibration solution, 500 mL		
HI 7033L	84 μS/cm calibration solution, 500 mL		
HI 7039L	5000 μS/cm calibration solution, 500 mL		
ACCESSORIES			

HI 710009	Shockproof rubber boot
HI 710010	Shockproof rubber boot
HI 710001	Soft carrying case
HI 721313	Rugged carrying case

NT (주) 뉴텍계기 서울특별시 금천구 가산동 60-15 리더스타워 501호 02-868-8648(대) sales@yesnt.co.kr www.yesnt.co.kr

## www.hannainst.com