

EC and Resistivity Meter

- Automatic temperature compensation (ATC)
- One-point calibration
- Help feature
 - On-screen user guides
- Waterproof

The HI87314 is a combination, portable meter that can read conductivity in four different ranges and resistivity.

For conductivity measurements, a one-point calibration is performed via a trimmer located in the battery compartment. The supplied probe does not require recalibration when switching from one range to another. The four-ring stainless steel probe has a built-in temperature sensor that automatically compensates for temperature changes. The temperature coefficient can be adjusted from 0 to 2.5%/°C using a knob on the front panel.

For resistivity measurements, the meter is factory calibrated and, if necessary, calibration can be adjusted. The HI3316D resistivity probe is easy to clean and requires little maintenance. It also features a built-in temperature sensor to automatically compensate for temperature variations. The temperature coefficient is user-selectable from 2 to 7%/°C.



Specifications

HI87314

| | | |
|---------------------------|--|--|
| EC | Range | 199.9 $\mu\text{S}/\text{cm}$; 1999 $\mu\text{S}/\text{cm}$; 19.99 mS/cm ; 199.9 mS/cm |
| | Resolution | 0.1 $\mu\text{S}/\text{cm}$; 1 $\mu\text{S}/\text{cm}$; 0.01 mS/cm ; 0.1 mS/cm |
| | Accuracy (@25°C/77°F) | ±1% F.S. |
| Resistivity | Range | 0 to 19.90 $\text{M}\Omega\cdot\text{cm}$ |
| | Resolution | 0.10 $\text{M}\Omega\cdot\text{cm}$ |
| | Accuracy (@25°C/77°F) | ±2% F.S. |
| Additional Specifications | Calibration | manual, one point, for both EC and resistivity |
| | Temperature Compensation | automatic from 0 to 50°C with β selectable from 0 to 2.5%/°C for EC and from 2 to 7%/°C for resistivity |
| | Probes | HI76302W conductivity probe with internal temperature sensor, DIN connector and 1 m (3.3') cable; HI3316D resistivity probe with internal temperature sensor, DIN connector and 1 m (3.3') cable |
| | Battery Type / Life | 9V / approximately 100 hours of use |
| | Environment | 0 to 50°C (32 to 122°F); RH max 100% |
| | Dimensions | 145 x 80 x 36 mm (5.7 x 3.1 x 1.4") |
| | Weight | 230 g (8.1 oz.) |
| Ordering Information | HI87314 is supplied with HI76302W conductivity probe, HI3316D resistivity probe, HI70030 calibration solution sachet, calibration screwdriver, battery, instructions and hard carrying case. | |

NT (주)뉴텍계기

서울특별시 금천구 가산동 60-15 리더스타워 501호
02-868-8648(대) sales@yesnt.co.kr www.yesnt.co.kr