



- |                                |                         |
|--------------------------------|-------------------------|
| 1 Resistive 5-inch Touchscreen | 3 Cylinder Locking Ring |
| 2 Glass Cylinder               | 4 Protective Enclosure  |

**Copley Scientific Limited**  
Colwick Quays Business Park, Road No.2,  
Nottingham, NG4 2JY, United Kingdom

### Physical Specifications

Model:	JV 100i	JV 200i
No. Test Stations	1	2
Test Methods Supported	USP <616> and Ph.Eur. (2.9.34) 1, 2, 3	USP <616> and Ph.Eur. (2.9.34) 2, 3
Unit Dimensions (w x d x h)	260 x 347 x 562 mm (with 250 mL cylinder)	260 x 347 x 562 mm (with 250 mL cylinder)
Mass (kg)	12	13
Max Noise Level @ 1 m	88.5 dB(A) 300 TPM, 14 mm drop, 250 mL cylinder	84.6 dB(A) 60 TPM, 14 mm drop, 250 mL cylinder

### Technical Specifications

Model:	JV 100i	JV 200i
Tap Frequency	50 to 300 TPM $\pm$ 5 TPM	
Test Run Time	0 to 99 H: 59 M: 59 S $\pm$ 1 % (1 S)	
Operating Temperature	15 °C to 30 °C	
Humidity	10 % to 85 % (non-condensing)	
Mains Supply	100 - 240 V, 50/60 Hz	
Isolation Classification	Class 1 - MUST BE EARTHED	
Power Consumption	Less than 75 W	
Fuses	2 x 2 A (Type T)	
Data Output	RS-232 USB A (For connection with a USB printer) USB B (for connection with a PC)	